



# Dortite® Xtra

## Premium Closed-cell Gasketing

Dortite® Xtra is a closed-cell blended neoprene expanded cellular rubber with an aggressive rubber based adhesive.

### Features

- Lightweight
- Economical
- Water Resistant
- Easy to Use

### Uses

Weather Stripping, Sound Vibration Dampening, Cushioning, Dust Proofing and Insulating

### Technical Data

Color	Black
Polymer	Neoprene/EPDMBlend
Compression/Deflection	5 – 9 psi
Density (P.C.F.) Average	7
Water Absorption by Weight	5%
	10% Allowed
Temperature Range	-20° to 200°F [-28° to 93°C]
Tensile Strength, Min.	120 psi
Elongation %, Min.	150
<b>Sizes</b>	
Thickness	1/8", 3/16", 1/4", 5/16", 3/8", 7/16" and 9/16" [3, 5, 6, 8, 10, 11 and 14 mm]
Width	1/4" to 40" [6 to 1016 mm]
Roll Length	25' and 50' [7.62 and 15.24 m]

### Specifications

ASTM D 1056-67 & 68	
Grade #	SCE42
ASTM D 1056-91 & 07	
SAE J18-R7/92	2C2
UL94 HF1, FMVSS302	Pass
UL 157	Pass
Standard for Safety for Gaskets and Seals	
UL 508	Pass
Standard for Safety for Industrial Control Equipment	
UL 50E	Pass
Standard for Safety for Enclosures for Electrical Equipment	

### Application

Temperature	Above 40°F [4°C]
Method	Trim to Size; Remove Release Liner and Apply to a Clean Dry Surface
Preparation	Surface Should be Dry, Clean from Oils and Debris

### Storage

Temperature	Moderate Conditions
Shelf Life	1 Year

